



OSOPLUS EXTREME PRO IV

FULLY SYNTHETIC

5W40 API SN/CF, ILSAC GF4

OSOPLUS EXTREME PRO IV is our top range Synthetic Engine Oil specially formulated with very high viscosity Synthetic Base Oil with latest advance additive chemistry delivery superior all round performance. Wear protection and cleaning power in even the most severe driving conditions.

With extensive field, racetrack and testing experiences over many years, **OSOPLUS EXTREME PRO IV** has been developed with the OSOPLUS Racing team in mind, to deliver the ultimate performance lubricant that provide complete engine protection. Especially for engines operating under the most demanding operating conditions through today's long drain interval.

APPLICATIONS

OSOPLUS EXTREME PRO IV are design to provide superior overall performance for latest engine technologies of high performance engines.

SPECIFICATIONS

API	SN/CF
ACEA	A3/B3, A3/B4
VW	505.00 / 501.01
MB	229.1

PRODUCT TYPICALS

CHARACTERISTICS	EXTREME PRO IV
SAE Viscosity Grade	5W40
Density @ 15°C kg/1	0.855
Flash Point °C	230
Pour Point °C	-38
Viscosity @ 40°C (cst)	93.5
@ 100°C (cst)	14.5
Viscosity Index	170
Cold Cranking Visc @ -35°C (cP)	4,682
Sulphated Ash, %wt	0.67
TBN (mgKOH/g)	8
Color	3.5

CUSTOMER BENEFITS

- Excellent low temperature for rapid ignition and protection.
- Excellent oxidation and thermal stability for normal and occasional severe operating conditions.
- Excellent wear protection of engine components.
- Excellent frictional capabilities that aids fuel economy, reduce vibration.
- Excellent clean engine with cleansing chemistry.

CUSTOMER ADVICE : For further assistance on product MSDS, recommended or technical queries, please liaise with the regional technical services engineer or contact HQ.

CAUTION : Do not ingest, if this should occur, drink large volumes water and seek medical attention. Always keep container cap sealed when not in use. keep out of reach of children

www.osoplus.com.my

2018 Osoplus Sdn. Bhd. – All Right Reserved

Furnishing the information contained herein does not constitute a representation by Osoplus Lubricants that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Osoplus Lubricants or any third party. Osoplus Lubricants assumes no liability for any infringement arise out of the use of the product. The information and suggestions for use and application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestion, and user urged to conduct confirmatory test to determine final suitability for their specific and uses. Osoplus Lubricants warranty only its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS