

# OSOPLUS PREMIUM IV

## MINERAL

### 15W40 API SN/CF

**OSOPLUS PREMIUM IV** is the latest generation premium mineral high performance multigrade engine oil specially engineered to provide the ultimate protection and performance for current and future generation high performance engine especially those fitted with emission control devices running the most extreme, most demanding driving conditions. It is exclusively formulated with premium mineral base fluid and high performance additive package system that provide exceptional thermal and oxidation.

**OSOPLUS PREMIUM IV** provides outstanding performance and excellent engine protection operating under the most severe operating condition throughout today's long drain interval. In addition to offering superior engine protection for all driving condition.

#### APPLICATIONS

**OSOPLUS PREMIUM IV** give superior all round performance on today's passenger motor cars where API classifications as exceeding API SN, equipped with the latest emission control and turbochargers.

#### SPECIFICATIONS

API	SN/CF
GM	6094M
SERVICE FILL	HONDA, NISSAN, MAZDA, KIA, HYUNDAI, PERODUA, PROTON

#### PRODUCT TYPICALS

CHARACTERISTICS	PREMIUM IV
SAE Viscosity Grade	15W40
Density @ 15°C,kg/l	0.886
Flash Point °C	225
Pour Point °C	-25
Kinematic Viscosity @ 40°C (cst)	107.8
@ 100°C (cst)	14.3
Viscosity Index	135
Cold Cranking Visc @ -35°C (cP)	6350
Sulphated Ash,%wt	-
TBN (mgKOH/g)	6
Color	2.5

#### CUSTOMER BENEFITS

- Provide excellence overall performance.
- Superior thermal and oxidation stability for extended oil change interval.
- Fortified friction technology for smoother and quieter drive.
- Rapid oil flow for easy ignition and fuel economy.
- High shear stability to maintain viscosity and stay on grade

CUSTOMER ADVICE : For further assistance on product MSDS, recommended or technical queries, please liaise with the regional technical services engineer or contact HQ.

CAUTION : Do not ingest, if this should occur, drink large volumes water and seek medical attention. Always keep container cap sealed when not in use. keep out of reach of children

[www.osoplus.com.my](http://www.osoplus.com.my)

2018 Osoplus Sdn. Bhd. – All Right Reserved

Furnishing the information contained herein does not constitute a representation by Osoplus Lubricants that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Osoplus Lubricants or any third party. Osoplus Lubricants assumes no liability for any infringement arise out of the use of the product. The information and suggestions for use and application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestion, and user urged to conduct confirmatory test to determine final suitability for their specific and uses. Osoplus Lubricants warranty only its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS